

UBCD436-PT DIGITAL SCANNER.

TECHNICAL SPECIFICATIONS - UBCD436-PT

Band Coverage : 31 Bands

Size: 2.8 in (W) x 1.5 in (D) x 6.3 in (H) (without antenna)

71.1 mm (W) x 36.9 mm (D) x 160.9 mm (H) (without antenna)

Weight: 12.3 oz. (with antenna and battery)

Operating Temperature: + 14° F (– 10° C) to + 140° F (+ 60° C)
(Charging Operation Temperature: +10° C to +40° C)

Storage Temperature: – 22° F (– 30° C) to + 158° F (+ 70° C)

Power Requirements: 3 X AA Rechargeable Ni-MH Batteries (2300mAh) (included)
3 X AA Alkaline Batteries (not included)
DC 5.0V ±5%. Connect to PC with USB cable (included)

LCD Display: 192 X 160 Full Dot Matrix LCD with white-color backlight.

Internal Speaker: 24ohm, 0.8W Max.

Certified in accordance with AS/NZS CISPR 22:2009 as of date of manufacture.

Weather Channels: 7 Channels

Scan Rate: 85 channels/second

Search Rate: 80 steps/second (12.5kHz step)
250 steps/second (5kHz step)

Scan Delay: 2 seconds

Audio Output Power: Internal Speaker - 360mW nominal
(24ohm)

Headphone (L-ch) 4mW nominal
(32 ohm)

Antenna: 50 ohms (Impedance)

INCLUDED WITH YOUR SCANNER

Accessories included in the box are:

UBCD436-PT	UBCD536-PT
USB Connection Cable	AC Power Adapter
3 X AA NiMH Rechargeable Batteries	Cigarette Lighter Power Cord
microSD card (installed)	USB Connection Cable
Swivel Belt Clip (attached)	microSD card (installed)
SMA-BNC Antenna Adaptor	DIN-E sleeve (optional accessory)
Rubber Antenna	DC Cord with Orange Wire
AC Adaptor	Mounting Bracket with screw and foot
DC Adaptor	Telescopic Antenna

UBCD436-PT

